

轻荷载脚轮

TP3000 系列

FEATURES

特征

顶板: 2.3t钢板
 支架: 1.6t钢板
 转环: 上 3/16" & 下 5/32" 钢珠
 旋转中心大小: Ø8.0
 轴: 1/4"(M6) 螺栓和螺母

用处

各种办公家具
 音响设备
 I.V Stand
 医用设备
 Pipe Rack



SERIES



WHEEL OPTION

SR 软橡胶轮	HR 硬橡胶轮	PLY 聚氨酯轮	MIR 高级橡胶轮	NYL 尼龙轮
				
尺寸 2" (50mm) 2 1/2" (64mm) 3" (76mm)	尺寸 2" (50mm) 2 1/2" (64mm) 3" (76mm)	尺寸 1 1/2" (38mm) 2" (50mm) 3" (76mm)	尺寸 2" (50mm) 3" (76mm)	尺寸 1 1/2" (38mm)

型号说明

万向	轮径(mm)	轮宽(mm)	轮子种类	轴承	载重Kg	旋转半径mm
TP3015-**-PLY NYL	1 1/2 (38)	23/32(18)	聚氨酯	无	30	39
			尼龙		35	
TP3020-**-SR HR PLY NYL MIR	2 (50)	13/16 (20)	软橡胶	无	35	45
			硬橡胶		40	
			聚氨酯		35	
			尼龙		40	
			橡胶 / 塑料		30	
TP3025-**-SR HR MIR	2 1/2 (64)	13/16 (20)	软橡胶	无	35	53
			硬橡胶		45	
			橡胶 / 塑料		35	
TP3030-**-SR HR PLY MIR	3(76)	13/16 (20)	软橡胶	无	40	60
			硬橡胶		50	
			聚氨酯		45	
			橡胶 / 塑料		40	

STEM OPTION

序号	类型	规格	安装高度(m/m)			
		(m/m)	1.5"(38)	2"(50)	2 1/2"(64)	3"(76)
01	长方形	整体尺寸 52 x 32	56	67	79	92
		孔距 40 x 21				
		安装孔尺寸 M4(3/16")				
11	环形	Ø11 x 30mm	56	67	79	92
12		Ø11 x 36mm				
14		Ø11 x 326.4mm				
21	丝杆型	1/2" x 12 \square x 16mm	61	72	85	98
24		3/8" x 16 \square x 32mm	58	68	81	94
2A		M12 x 1.75P x 16mm	66	68	81	94

OPTION

SLB	TLB	FLB	CR
			
边刹	边刹	前刹	镀铬