

轻荷载脚轮

TP3600 系列

FEATURES

特征

顶板: 3.0t钢板
 支架: 2.3t钢板
 转环: 上 1/4" & 下 3/16" 钢珠
 旋转中心大小: Ø11.0
 轴: 5/16"(M8)

用处

医疗设备
 轻重量搬运车
 其它工业用搬运车



SERIES



WHEEL OPTION

SR 软橡胶轮	HR 硬橡胶轮	PLY 聚氨酯轮	MIR 高级橡胶轮	LDP 重型塑料轮
				
尺寸 2 1/2" (64mm) 3" (76mm) 4" (102mm) 5" (127mm)	尺寸 2 1/2" (64mm) 3" (76mm) 4" (102mm) 5" (127mm)	尺寸 2 1/2" (64mm)	尺寸 2 1/2" (64mm) 3" (76mm) 4" (102mm) 5" (127mm)	尺寸 3" (76mm) 4" (102mm)

型号说明

万向	定向	轮径(mm)	轮宽(mm)	轮子种类	轴承	载重Kg	安装高度	旋转半径
		规格 (m/m)						
TP3625-**-SR HR PLY PLY TG MIR TG	TP3625-**-SR HR PLY PLY TG MIR TG	2 1/2 (64)	1(25)	软橡胶	无	35	84	57
				硬橡胶		45		
				聚氨酯	滚珠	40		
				聚氨酯		45		
				橡胶 / 塑料		55		
TP3630-**-SR HR LDP MIR MIR TG	TP3630R-SR HR LDP MIR MIR TG	3 (76)	1(25)	软橡胶	无	45	95	66
				硬橡胶		55		
				轻型塑料		65		
				橡胶 / 塑料		55		
				橡胶 / 塑料		55		
TP3640-**-SR HR LDP MIR MIR TG	TP3640R-SR HR LDP MIR MIR TG	4(102)	1(25)	软橡胶	无	55	120	80
				硬橡胶		60		
				轻型塑料		80		
				橡胶 / 塑料		60		
				橡胶 / 塑料		60		
TP3650-**-SR HR MIR	TP3650R-SR HR MIR	5(127)	1(25)	软橡胶	无	60	146	94
				硬橡胶		65		
				橡胶 / 塑料		65		

STEM OPTION

序号	类型	规格 (m/m)				
		分	整体尺寸	孔距	安装孔尺寸	
01	长方形	2 1/2"	万向	70 x 60	55 x 42	M8 (5/16")
			定向	70 x 47	55 x 28	
		3"~5"	95 x 70	76 to 73 x 45		
11	环形	Ø11 x 38mm				
13		Ø22.5 x 56mm				
21	丝杆形	1/2" x 12山 x 16mm				
22		7/16" x 14山 x 57mm				
23		5/8" x 11山 x 32mm				
24		5/8" x 11山 x 20mm				
29		1/2" x 12山 x 35mm				
2A		M12 x 1.75P x 20mm				
32	圆柱形	Ø16 x 87mm - Ø7 孔				

OPTION

TLB	CR
	
边刹	镀铬