

重荷载脚轮

TP6200 系列

FEATURES

特征

顶板: 4.0t钢板
支架: 4.0t 钢板
转环: 上 1/4" & 下 7/32" 钢珠
旋转中心大小: Ø12.0
轴: 1/2" (M12) 螺栓和螺母

用处

PIPE RACK 推车
各种重载物品搬运车



SERIES



WHEEL OPTION

RCI	PCI	PRO
		
尺寸 4" (102mm) 5" (127mm) 6" (152mm)	尺寸 4" (102mm) 5" (127mm) 6" (152mm)	尺寸 4" (102mm) 5" (127mm) 6" (152mm)

MODEL DESCRIPTIONS

万向	定向	轮径(mm)	轮宽(mm)	轮子种类	轴承	承重Kg	安装高度	旋转半径
TP6240-**-RCI TG PCI TG PRO TG	TP6240R-RCI TG PCI TG PRO TG	4(102)	1 1/2 (38)	橡胶/铁	滚轴 (#001)	110	136	86
				聚氨酯/铁		220		
				聚氨酯/塑料		130		
TP6250-**-RCI TG PCI TG PRO TG	TP6250R-RCI TG PCI TG PRO TG	5(127)	1 1/2 (38)	橡胶/铁		130	161	104
				聚氨酯/铁		250		
				聚氨酯/塑料		150		
TP6260-**-RCI TG PCI TG PRO TG	TP6260R-RCI TG PCI TG PRO TG	6(152)	1 1/2 (38)	橡胶/铁		130	191	118
				聚氨酯/铁		250		
				聚氨酯/塑料		180		

STEM OPTION

序号	类型	规格(m/m)
01	长方形	整体尺寸 97 x 86
		孔距 76 x 58 to 68 x 66
		安装孔尺寸 M10 (3/8")
02		整体尺寸 114 x 102
		孔距 92 x 67 to 76 x 76
		孔尺寸 M10 (3/8")
05		整体尺寸 107 x 120
		孔距 60 to 72 x 68
		孔尺寸 M10 (3/8")

OPTION

