

轻荷载脚轮

TP4000 系列

FEATURES

特征

顶板: 1.6~3.2t 钢板
 支架: 1.6~3.2t 钢板
 转环: 5/32" & 3/8" 钢珠
 旋转中心大小: $\varnothing 6.0 \sim \varnothing 14.0$
 轴: $\varnothing 5.0$ 铆钉 ~ 7/16" 螺栓和螺母

用处

轻型搬运车
 商场展示架
 电子机器



SERIES



WHEEL OPTION

SR	HR	HDP	PLY	LDP	AL	NYL
						
尺寸2" (50mm)	尺寸2" (50mm)	尺寸3" (76mm)	尺寸 1 1/4" (32mm) 1 1/2" (40mm) 2" (50mm)	尺寸3" (76mm)	尺寸2" (50mm)	尺寸 1 1/2" (40mm) 2" (50mm)



MODEL DESCRIPTIONS

方向	定向	轮径(mm)	轮宽(mm)	轮子种类	轴承	承重Kg	安装高度	旋转半径
TP4011-01-NYL		1 1/8 (29)	9/16 (14)	尼龙	无	14	39	22
TP4012-**-PLY	TP4012R-PLY	1 1/4 (32)		聚氨酯		14	43	28
TP4015-**-NYL PLY	TP4015R-NYL PLY	1 1/2 (40)	23/32 (18)	尼龙		28	54	40
TP4020-**-PLY	TP4020R-PLY	2 (50)	1 (25)	聚氨酯		40	63	44
NYL	NYL			尼龙		55		
AL	AL			铝		57		
SR	SR			软橡胶		40		
HR	HR			硬橡胶		57		
TP4025-01-SR	TP4025R-SR	2 1/2 (64)	1 1/16(27)	软橡胶		45	83	61
HR	HR			硬橡胶		45		
PLY	PLY			聚氨酯	45			
NYL	NYL			尼龙	80			
TP4030-01-SR	TP4030R-SR	3 (76)	1 1/4(32)	软橡胶	无	56	96	69
SRB	SRB			软橡胶	滚珠	110		
HR	HR			硬橡胶	无	100		
HRB	HRB			硬橡胶	滚珠	110		
PLY TG	PLY TG			聚氨酯	滚珠	100		
PLY	PLY			聚氨酯	无	65		
LDP	LDP			轻型塑料	无	100		
HDP	HDP			重型塑料	无	110		

STEM OPTION

	轮子直径	整体尺寸	孔距	安装孔尺寸
	Inch(m/m)	(m/m)	(m/m)	(m/m)
方向	1 1/8"(29)-01	45 x 30	35 x 20	M4(5/32")
	1 1/4"(32)-01	60 x 30	44	M4(5/32")
	02	45 x 30	35 x 20	M4(5/32")
	1 1/2"(40)-01	55 x 38	44 x 27	M4(5/32")
	05	100 x 70	82 x 50	M4(5/32")
	06	55 x 38	44 x 27	M5(3/16")
	2 (50)-01	65 x 48	54 x 24	M6(1/4")
	05	100 x 70	82 x 50	M4(5/32")
定向	2 1/2"(64)	98 x 70	76 x 45	M8(5/16")
	3 (76)	104 x 79	86 x 60	M8(5/16")
	1 1/4"(32)	60 x 25	44	M4(5/32")
	1 1/2"(40)	55 x 38	44 x 27	M4(5/32")
	2 (50)	68 x 38	54 x 24	M6(1/4")
	2 (50)-04	68 x 38	54	M6(1/4")
	2 1/2"(64)	113 x 57	89 x 27	M8(5/16")
3 (76)	125 x 63	102 x 30	M8(5/16")	

OPTION

SLB	TG
	
边刹	防尘盖